





Legend LPX | Lightbar

- Solaris_® LED Reflector Technology
- ROC (Reliable Onboard Circuitry™) technology
- FS Convergence Network for "plug-and play" installation
- All-LED lightbar LED Alleys and LED Takedowns available
- LED colors available in Amber, Blue, Red, Green, or White

- Top dome covers available in Amber, Blue, Red or Clear
- Available in 45-, 53-, 61-, 70-inch lengths
- Optional built-in SignalMaster, front/rear cut-off, intersection warning, and "dimming" functions
- Same flash patterns and controller options as standard Legend lightbars
- Five-year LED warranty

• SAE J845 - Red and Amber warning lights meet Class 1, Blue meet Class 2

 SAE J595 – Red and Amber warning lights meet Class 1. Blue meet Class 2

New Legend LPX Series offers many of the same premium features found on high-end lightbars at a surprisingly moderate cost.

The low-profile LPX Series is the latest addition to the highly respected Legend lightbar line, and employs powerful LEDs in tandem with Federal Signal's exclusive Solaris_® reflector technology to supply 360-degree of coverage plus superior off-axis light output.



ROC (Reliable Onboard Circuitry...) technology ensures optimum reliability by eliminating 85% of the failure points common to conventional lightbar designs.

Ruggedly built to withstand the most punishing conditions, these solid-state lightbars are engineered to supply extended service life with fewer repairs. That's why the LPX Series carries Federal Signal's five-year warranty on LEDs.

The LPX Series showcases many of the same features typically found on lightbars costing substantially more.

This includes LED alley and takedown lights, front and rear light cut-off control, and a dimming feature to reduce light output when the vehicle is stationary. In addition to providing flash patterns and controller options as standard Legend lightbars, LPX models also feature Federal Signal's patented Convergence Network for "plug-and-play" programming to facilitate faster, easier installation and maintenance.

It's your call: 45-, 53-, 61-, 70-inch lengths...Amber, Blue, Red, Green and White LEDs...Amber, Blue, Clear and Red top domes.

Legend LPX delivers a host of options such as a built-in SignalMaster directional warning control, ultra-bright white takedown lights and either a three- or six-button serial controller for variable light control.







Network



SPECIFICATIONS

Specifications

To order, choose one of the preselect models shown below or utilize Federal Signal's on-line configurator www. config.fedsig.com/lightbar to customize your own lightbar.

Select Model

LPX45-00009 Red/Blue, (2) LED alley lights, (2) LED

takedowns, (2) Red corner LED reflectors, (5) Red LED reflectors, (2) Blue corner LED reflectors, (5) Blue LED reflectors, interface

module, Black hook mount

LPX45-00010 Red/Blue, (2) LED alley lights, (2) LED

takedowns, (2) Red corner LED reflectors, (2) Red LED reflectors, (2) Blue corner LED reflectors, (2) Blue LED reflectors, (6) Amber LED reflectors, interface module,

Black hook mount

LPX45-00019 Amber, (18) Amber LED reflectors,

6-button controller, flat mount

LPX45-00020 Amber, (14) Amber LED reflectors, (2) LED

takedowns, 6-button controller, flat mount

LPX53-00018 Red/Blue, (2) LED alley lights, (2) LED

takedowns, (2) Red corner LED reflectors, (3) Red LED reflectors, (2) Blue corner LED reflectors, (3) Blue LED reflectors, (8) Amber LED reflectors, interface module,

Black hook mount

LPX53-00019 Red/Blue, (2) LED alley lights, (2) LED

takedowns, (2) Red corner LED reflectors, (7) Red LED reflectors, (2) Blue corner LED reflectors, (7) Blue LED reflectors, interface

module, Black hook mount

RED DOME				BLUE DOME			
¢.R c∈	R	R	LED TD	LED TD	В	В	B &
LED AL	R	R	R	В	В	В	B &
LPX45-00009							

	RED DOME			CLEAR DOME			BLUE DOME		
R EED AL	R	R	LED TD	R	В	LED TD	В	В	B & LED AL
₽ R	A	A	A	A	A	A	A	A	B ®


LPX53-00018


CLEAR DOME				CLEAR DOME			
A A	Α	Α	Α	Α	Α	Α	AA
Α							A
A A	A	A	A	A	A	Α	A A

LPX45-00019

Specifications								
	45"	53"	61"	70"				
Voltage	12.8 VDC	12.8 VDC	12.8 VDC	12.58 VDC				
Current Draw	Per Li	ghting Option	ns (all four m	odels)				
LED Takedown	1.0A**	1.0A**	1.0A**	1.0A**				
Alley Light	2.7A*	2.7A*	2.7A*	2.7A**				
Solaris LED - Main Lightbar	1.0A**	1.0A** 1.0A**		1.0A**				
Physical Specifications								
Height		2.5 in (6.4 cm)					
Length	44.5 in (113.0cm)	52.7 in (133.9cm)	60.9 in (154.7cm)	69.1 in (175.5cm)				
Width		11.2 in	(6.4 cm)					
Ship We	ight							
	20.4 lb (9.2 kg)	. 5.		. 3.				

- * Amperage per pair, with flashing takedown and alley lights
- ** Amperage in steady burn mode





LPX53-00019

CLEAR DOME				CLEAR DOME			
A A	A	LED TD	A	A	LED TD	A	A A
LED AL	A	A	A	A	A	A	LED AL

LPX45-00020

Legend, Solaris, Reliable Onboard Circuity, and SignalMaster are trademarks of Federal Signal Corporation.

©2016 Federal Signal Corporation. M1031 I 316

